





General

Many thermal processes use rotating kilns to clean soil, to burn waste, or to sinter ceramic products. Prevent high costs and protect your rotating kiln with our **Wearflex® dynamic seals**.

Traditional seals are stiff and wear out on the largest diameter as long cylindrical rotating kilns are not always perfectly round. This causes air ingress because of negative pressure.

As a result, the firing process is being disturbed, COx- and NOxemissions increase and the use of energy rises, with all the costly consequences. To prevent these problems, our engineers developed **Wearflex® dynamic seals**.

Wearflex[®] dynamic seals follow the shape of the rotating kiln. They reduce cold air ingress and create a better sealing between the rotating and the static part of the application. This results in less air ingress, less COx- and NOx-emissions, less fuel consumption and a better control of your thermal process.

Advantages Wearflex® dynamic seals

- Better control of your thermal process, which results in better products
- Less COx and NOx emissions
- Less fuel consumption

07122021

INSULCON N.V. – Belgium +32 (0) 3 711 02 78 insulconnv@insulcon.com

CONTACT

INSULCON B.V. – The Netherlands

+31 (0) 167 565750 info@insulcon.com

INSULCON GmbH - Germany +49 (0) 2131 408548-0 insulcongmbh@insulcon.com

INSULCON PROJECTS S.A. - Switzerland +41 (0) 91 911739 infoch@insulcon.com



www.insulcon.com / www.wearflex.com